

WHEELS

Product group	Wheels
Item number	10001874
Valid wheel size	215 / 75 R 17.5
Brand	Windpower
Tread pattern	WGC 28
Valid rim size	6.75 x 17.5
Rim connection	8/221/275
Bolt hole design	M22
Offset (mm)	+55
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	100



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466409
LI / SI / PR	135 / 133 J, 18 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	100
Load capacity 3 [kg]	2060
Speed 3 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	54,43
ECE regulation number	ECE 54 ECE 117
Section width (mm)	218
Stat. radius (SLR) [mm]	358
Rolling circumference [mm].	2336
Tread depth (mm)	15,5
Rolling resistance	E
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10000221
Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	120
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12.0
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB

Number of bolt holes	8
Bolt hole diameter [mm]	24
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade