

WHEELS

Product group	Wheels
Item number	10001875
Valid wheel size	405 / 70 R 20
Brand	BKT
Tread pattern	Multimax MP 513
Valid rim size	W 13 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	2240
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15735230
LI / SI / PR	136 G
Load capacity 1 [kg]	2240
Speed 1 [km/h].	90
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,60
ECE regulation number	ECE 54
Section width (mm)	407

Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3253
Tread depth (mm)	29,0
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 33060164
Load capacity of rim 1 [kg]	4750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,50
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade