

TYRES

Product group	Tyres
Item number	10001891
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	141 A8 / 153 A8
TL/TT	TL
Brand	BKT
Tread pattern	AS 509





Notes and features

- The BKT AS509 was specially developed for agricultural trailers, seeders and soil cultivating machines
- The high number of lugs provides optimal ground pressure distribution
- The tyre guarantees high loading capacity with low inflation pressure for minimal soil compaction



Technical Informations

Item number	10001891
EAN	8903094064878
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	141 A8 / 153 A8
TL/TT	TL
Brand	BKT
Tread pattern	AS 509
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	70,03
Recommended rim size	AG16.00
Maximum air pressure [bar].	2,10
Section width (mm)	540
Outer diameter of tyre [mm].	1065
Stat. radius (SLR) [mm]	479
Dynamic radius [mm]	3250
Rolling circumference [mm].	3250
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40	Drive Wheel	2,10	
153 A8	3650	40	Free Rolling	2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.