

TYRES

Product group	Tyres
Item number	10001899
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 115 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 II is a standard radial tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

Technical Informations

Item number	10001899
EAN	8714692344664
Valid tyre size	280 / 85 R 24
Alternative size 1	11.2R24
LI / SI / PR	115 A8 / 115 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	46,88
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	1,60
Section width (mm)	290
Outer diameter of tyre [mm].	1085
Stat. radius (SLR) [mm]	505
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3220
Tread depth (mm)	38,0
Tyre capacity 75% [litr.]	75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40		1,60	
115 B	1215	50		1,60	