

TYRES

Product group	Tyres
Item number	10001904
Valid tyre size	460 / 85 R 38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 II is a standard radial tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

Technical Informations

Item number	10001904
EAN	8714692623776
Valid tyre size	460 / 85 R 38
Alternative size 1	18.4R38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	149,94
Recommended rim size	DW16L
Permitted rim size	(D)W14L, (D)W15L, W16L
Maximum air pressure [bar].	1,60
Section width (mm)	490
Outer diameter of tyre [mm].	1755
Stat. radius (SLR) [mm]	790
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5195
Tread depth (mm)	49,0
Tyre capacity 75% [ltr.]	365
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
149 B	3250	50		1,60	