

TYRES

Product group	Tyres
Item number	10001909
Valid tyre size	420 / 85 R 30
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II





Notes and features

- The Traxion 85 II is a standard radial tractor tyre for midrange tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life



Technical Informations

Item number	10001909
item number	100013003
EAN	8714692344824
Valid tyre size	420 / 85 R 30
Alternative size 1	16.9R30
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	104,27
Recommended rim size	DW15L
Permitted rim size	DW13, (D)W14L, W15L
Maximum air pressure [bar].	1,60
Section width (mm)	450
Outer diameter of tyre [mm].	1470
Stat. radius (SLR) [mm]	660
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4330
Tread depth (mm)	47,0
Tyre capacity 75% [ltr.]	245
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		1,60	
140 B	2500	50		1,60	