

TYRES

Product group	Tyres
Item number	10001913
Valid tyre size	380 / 85 R 28
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 II is a standard radial tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

Technical Informations

Item number	10001913
EAN	8714692344770
Valid tyre size	380 / 85 R 28
Alternative size 1	14.9R28
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	81,87
Recommended rim size	W13
Permitted rim size	W11, W12(L), DW13(L)
Maximum air pressure [bar].	1,60
Section width (mm)	400
Outer diameter of tyre [mm].	1350
Stat. radius (SLR) [mm]	610
Speed Radius Index (SRI)	650
Rolling circumference [mm].	3980
Tread depth (mm)	44,0
Tyre capacity 75% [ltr.]	175
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,60	
133 B	2060	50		1,60	