

## **WHEELS**

Product group	Wheels
Item number	10001924
Valid wheel size	4.00 - 4
Brand	Kenda
Tread pattern	K373
LI / SI / PR	6 PR
титт	TT
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	20
Mounting length [mm]	75
Hub length [mm]	75
Rim colour	Silver
Load capacity complete wheel [kg]	300
Speed complete wheel [km/h]	20



## **Technical Informations**

Assembly Item no. Tyres	19211080
LI / SI / PR	6 PR
TL/TT	тт
Brand	Kenda
Tread pattern	K373
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	5,20
Section width (mm)	117
Rolling circumference [mm].	913
Assembly Item no. Rim •	10001768
Valid rim size	2.10 - 4
Load capacity of rim 1 [kg]	300
Speed Rims 1 [km/h]	20
Maximum speed [km/h].	20
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	geteilt
Quantity multi-piece	two-part
Rim material	steel
Surface treatment	coated
RAL	RAL9006
Colour type	Glossy
Disc thickness [mm]	2.0
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	11.0