

TYRES

Product group	Tyres
Item number	10001929
Valid tyre size	28 L - 26
LI / SI / PR	177 A2 / 165 A6, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 345



Notes and features

- The Alliance Forestar 345 was developed for use on heavy forestry machines and logging equipment operating in challenging conditions.
- The tyre provides high traction and low slip, even without chains.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls, the tyre is very tough and durable.
- Thanks to its high lugs and especially hard-wearing rubber compound, the tyre is optimally suited to demanding forest applications.
- It is the ideal tyre for skidders.

Technical Informations

Item number	10001929
EAN	8903635009603
Valid tyre size	28 L - 26
LI / SI / PR	177 A2 / 165 A6, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 345
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	315,20
Recommended rim size	DW25B
Maximum air pressure [bar].	2,40
Section width (mm)	715
Outer diameter of tyre [mm].	1638
Stat. radius (SLR) [mm]	749.3
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4959
Tread depth (mm)	58,9
Number of lugs	15x2
Tyre capacity 75% [ltr.]	568.72
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 A2	7300	10		2,40	
165 A6	5150	30		2,40	