

TYRES

Product group	Tyres
Item number	10001931
Valid tyre size	16.0 / 70 - 24
LI / SI / PR	14 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936



Notes and features

- Rugged tyre for mobile excavators in the harshest of operating conditions.
- Well-suited for road travel.
- Aggressive tread pattern for high traction and good self-cleaning properties.
- High level of stability in use and good handling on the road.

Technical Informations

Item number	10001931
EAN	8903094067053
Valid tyre size	16.0 / 70 - 24
LI / SI / PR	14 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936
TRA Code	E2
Carcass properties	Non-Marking
Antistatic	No
Tyre colour	Grey
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	76,87
Recommended rim size	13SDC
Permitted rim size	13DC
Maximum air pressure [bar].	4,50
Section width (mm)	404
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	575
Rolling circumference [mm].	3600
Tread depth (mm)	29,5
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	3550	50	Transport	3,50	
	5800	10	Loader dozer	4,50	