

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 10001932 |
| Valid tyre size | 12 - 16.5 |
| LI / SI / PR | 130 A8, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Skid Power SK |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- BKT's Skid Power SK tyre is a newly-developed wide-wall skid steer loader tyre.
- With sidewall and rim guard protectors, the Skid Power SK is ideal for performance-oriented and price-conscious use on skid steer loaders like the Bobcat and other similar vehicles.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 10001932 |
| EAN | 8903094067060 |
| Valid tyre size | 12 - 16.5 |
| LI / SI / PR | 130 A8, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Skid Power SK |
| Carcass properties | Non-Marking |
| Antistatic | No |
| Tyre colour | Grey |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 31,80 |
| Recommended rim size | 9.75 |
| Maximum air pressure [bar]. | 5,50 |
| Section width (mm) | 312 |
| Outer diameter of tyre [mm]. | 825 |
| Stat. radius (SLR) [mm] | 375 |
| Rolling circumference [mm]. | 2434 |
| Tread depth (mm) | 17,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 130 A8 | 1900 | 40 | | 5,50 | |