

WHEELS

Product group	Wheels
Item number	10001967
Valid wheel size	24 R 20.5
Brand	BKT
Tread pattern	Ridemax FL 699
Valid rim size	18.00 x 20.5
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	7100
Speed complete wheel [km/h]	80
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15717300
LI / SI / PR	176 F, 16 PR
Load capacity 1 [kg]	7100
Speed 1 [km/h].	80
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	253,14
ECE regulation number	ECE 54
Section width (mm)	590

Stat. radius (SLR) [mm]	613
Rolling circumference [mm].	4165
Tread depth (mm)	18,0
E-Ready	No
Assembly Item no. Rim	• 33060181
Load capacity of rim 1 [kg]	7100
Speed Rims 1 [km/h]	80
Maximum speed [km/h].	80
Maximum air pressure [bar].	6,00
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade