

## WHEELS

Product group	Wheels
Item number	10001969
Valid wheel size	425 / 55 R 17
Brand	BKT
Tread pattern	Multimax MP 513
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2120
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15735210
LI / SI / PR	134 G
Load capacity 1 [kg]	2120
Speed 1 [km/h].	90
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	77,10
ECE regulation number	ECE 54
Section width (mm)	421
Stat. radius (SLR) [mm]	399
Rolling circumference [mm].	2695

Tread depth (mm)	28,0
Number of lugs	17x2
E-Ready	No
Assembly Item no. Rim	• 33060081
Load capacity of rim 1 [kg]	4950
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,50
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7

---

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade