

WHEELS

Product group	Wheels
Item number	10001974
Valid wheel size	13 x 5.00 - 6
Brand	Deli
Tread pattern	S-247
Valid rim size	3.50 x 6 H2
Rim connection	4/60/90
Rim colour	Silver
Load capacity complete wheel [kg]	145
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	19110080
LI / SI / PR	29A6 / 41 A6, 4 PR
Load capacity 1 [kg]	103
Speed 1 [km/h].	30
Load capacity 2 [kg]	145
Speed 2 [km/h].	30
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	3,61
ECE regulation number	ECE 106
Section width (mm)	125

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Stat. radius (SLR) [mm]	153
Rolling circumference [mm].	961
Tread depth (mm)	9,4
E-Ready	No
Assembly Item no. Rim •	39600300
Load capacity of rim 1 [kg]	325
Speed Rims 1 [km/h]	16
Load capacity of rim 2 [kg]	145
Speed Rims 2 [km/h]	30
Maximum speed [km/h].	30
Maximum air pressure [bar].	2,10
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	1.75
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	8.5
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	90
Valve seat	External Valve
Valve hole diameter [mm]	11.3

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade