

## WHEELS

Product group	Wheels
Item number	10001975
Valid wheel size	13 x 5.00 - 6
Brand	Kenda
Tread pattern	K358 Turf Rider
Valid rim size	3.50 x 6 H2
Rim connection	4/60/90
Rim colour	Silver
Load capacity complete wheel [kg]	250
Speed complete wheel [km/h]	20



## Technical Informations

Assembly Item no. Tyres	• 19211121
LI / SI / PR	49 A4 / 60 A4, 6 PR
Load capacity 1 [kg]	185
Speed 1 [km/h].	20
Load capacity 2 [kg]	250
Speed 2 [km/h].	20
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	3,17
ECE regulation number	ECE 106
Section width (mm)	121

Rolling circumference [mm].	985
E-Ready	No
Assembly Item no. Rim	• 39600300
Load capacity of rim 1 [kg]	325
Speed Rims 1 [km/h]	16
Load capacity of rim 2 [kg]	145
Speed Rims 2 [km/h]	30
Maximum speed [km/h].	20
Maximum air pressure [bar].	4,20
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	1.75
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	8.5
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	90
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve

---

Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade