

WHEELS

Product group	Wheels
Item number	10001976
Valid wheel size	185 R 14 C
Brand	BK Trailer
Tread pattern	203
Valid rim size	6 J x 14 H2
Rim connection	6/161/205
Bolt hole design	E2
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 18545090
LI / SI / PR	104 / 102 N
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Load capacity 3 [kg]	850
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18,33
ECE regulation number	ECE 54 ECE 117

Section width (mm)	188
Stat. radius (SLR) [mm]	295
Rolling circumference [mm].	1979
Tread depth (mm)	6,0
Rolling resistance	D
Wet grip	D
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39800445
Load capacity of rim 1 [kg]	1250
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,48
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16

hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade