

## WHEELS

Product group	Wheels
Item number	10001994
Valid wheel size	11.5 / 80 - 15.3
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2900
Speed complete wheel [km/h]	30



## Technical Informations

Assembly Item no. Tyres	• 15211631
LI / SI / PR	145 A6 / 141 A8, 14 PR
Load capacity 1 [kg]	2900
Speed 1 [km/h].	30
Load capacity 2 [kg]	2575
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	36,17
ECE regulation number	ECE 106
Section width (mm)	290

Stat. radius (SLR) [mm]	364.8
Speed Radius Index (SRI)	400
Rolling circumference [mm].	2540
Tread depth (mm)	9,0
E-Ready	No
Assembly Item no. Rim	• 33060026
Load capacity of rim 1 [kg]	3450
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2900
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,70
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

---

<b>Bolt hole circle diameter [mm]</b>	205
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade