

TYRES

Product group	Tyres	
Item number	10001997	
Valid tyre size	380 / 55 - 17	
LI / SI / PR	122 A8 / 134 A8, 10 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AW 729	





Notes and features

- The BKT AW 729 is an implement tyre for agricultural trailers, hay harvesters, balers and soil tillage implements
- The rounded tyre shoulder and the tread pattern with 3 circumferential grooves in the tread centre ensure low soil compaction and prevent soil damage
- The tyre offers excellent performance in both field applications and on the road



Technical Informations

Item number	10001997
EAN	8903094074150
Valid tyre size	380 / 55 - 17
LI / SI / PR	122 A8 / 134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 729
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,96
Recommended rim size	13.00
Permitted rim size	13, W13
Maximum air pressure [bar].	2,60
Section width (mm)	385
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2560
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40	Drive Wheel	2,60	
134 A8	2120	40	Free Rolling	2,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.