

WHEELS

Product group	Wheels
Item number	10002000
Valid wheel size	445 / 65 R 22.5
Brand	Sailun
Tread pattern	S825
Valid rim size	14.00 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	5600
Speed complete wheel [km/h]	110



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066411
LI / SI / PR	168 K, 20 PR
Load capacity 1 [kg]	5600
Speed 1 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	162,42
ECE regulation number	ECE 54 ECE 117

Section width (mm)	444
Rolling circumference [mm].	3485
Tread depth (mm)	16,5
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10000373
Load capacity of rim 1 [kg]	6000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	5500
Speed Rims 2 [km/h]	130
Maximum speed [km/h].	110
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13.5
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole diameter [mm]	26.0

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No