

## **TYRES**

Product group	Tyres	
Item number	10002008	
Valid tyre size	405 / 70 R 24	
LI / SI / PR	152 J	
TL/TT	TL	
Brand	BKT	
Tread pattern	Multimax MP 540	





## **Notes and features**

- The BKT Multimax MP 540 was developed for multipurpose vehicles in municipality/maintenance applications.
- Thanks to its reinforced, steel belted nylon casing, the tyre provides high load capacity at high speeds.



## **Technical Informations**

Item number	10002008
EAN	8903094074600
Valid tyre size	405 / 70 R 24
LI / SI / PR	152 J
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 540
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	93,86
Recommended rim size	13
Maximum air pressure [bar].	5,00
Section width (mm)	402
Outer diameter of tyre [mm].	1174
Stat. radius (SLR) [mm]	530
Rolling circumference [mm].	3586
Tread depth (mm)	19,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 J	3550	100		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.