

WHEELS

Product group	Wheels
Item number	10002017
Valid wheel size	560 / 45 R 22.5
Brand	BKT
Tread pattern	FL 630 Ultra
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4875
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715113
LI / SI / PR	163 A8 / 152 D
Load capacity 1 [kg]	4875
Speed 1 [km/h].	40
Load capacity 2 [kg]	3550
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	142,71
ECE regulation number	ECE 106

Section width (mm)	543
Stat. radius (SLR) [mm]	490
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3290
Tread depth (mm)	28,5
Number of lugs	18x2
Tyre capacity 75% [ltr.]	247
E-Ready	No
Assembly Item no. Rim	• 10001304
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	8
Bolt hole design EUWA	B18 ES 32
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade