

WHEELS

Product group	Wheels
Item number	10002018
Valid wheel size	800 / 45 - 26.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	AG 28.00 x 26.5 H2
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712885
LI / SI / PR	164 A8 / 177 A8, 16 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	7300
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	260,83
ECE regulation number	ECE 106

Section width (mm)	800
Stat. radius (SLR) [mm]	581
Rolling circumference [mm].	4017
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 33060801
Load capacity of rim 1 [kg]	10300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,20
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1

Valve length [mm]	50.0
Valve angle [°]	gerade
