

TYRES

Product group	Tyres
Item number	10002026
Valid tyre size	285 / 80 R 16
LI / SI / PR	128 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

Technical Informations

Item number	10002026
EAN	8903094074471
Valid tyre size	285 / 80 R 16
LI / SI / PR	128 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	36,88
Recommended rim size	W10
Maximum air pressure [bar].	4,00
Section width (mm)	304
Outer diameter of tyre [mm].	866
Stat. radius (SLR) [mm]	394
Rolling circumference [mm].	2617
Tread depth (mm)	25,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 G	1800	90		4,00	