

TYRES

Product group	Tyres
Item number	10002027
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 153 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDM1



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun SDM1 is a radial truck tyre for construction site use.
- Its tread pattern offers very good traction and prevents small stones from penetrating the tread.
- The arrangement and stability of the tread blocks in the center of the tread ensure even wear.
- Small grooves between the blocks prevent the tyre from heating up.
- The high tread depth and the reinforced tyre bead increase its service life.

Technical Informations

Item number	10002027
EAN	6959655472769
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 153 K, 20 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDM1
M+S	M+S
3PMSF	3PMSF
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	69,00
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,50
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Rolling circumference [mm].	3282
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	8,50	
153 K	3650	110	Twin	8,50	