

TYRES

Product group	Tyres
Item number	10002028
Valid tyre size	325 / 70 R 18
LI / SI / PR	132 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.



Technical Informations

Item number	10002028
EAN	8903094074488
Valid tyre size	325 / 70 R 18
LI / SI / PR	132 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	43,55
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	3,50
Section width (mm)	322
Outer diameter of tyre [mm].	916
Stat. radius (SLR) [mm]	410
Rolling circumference [mm].	2771
Tread depth (mm)	25,5
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 G	2000	90		3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.