

## TYRES

Product group	Tyres
Item number	10002033
Valid tyre size	280 / 85 R 20
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	10002033
EAN	8903094072927
Valid tyre size	280 / 85 R 20
Alternative size 1	11.2 R 20
LI / SI / PR	122 A8 / 122 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
TRA Code	R1-W
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	36,16
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	2,40
Section width (mm)	292
Outer diameter of tyre [mm].	984
Stat. radius (SLR) [mm]	447
Speed Radius Index (SRI)	475
Rolling circumference [mm].	2977
Tread depth (mm)	37,5
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40		2,40	
122 B	1500	50		2,40	