

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10002033 |
| Valid tyre size | 280 / 85 R 20 |
| LI / SI / PR | 122 A8 / 122 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 855 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10002033 |
| EAN | 8903094072927 |
| Valid tyre size | 280 / 85 R 20 |
| Alternative size 1 | 11.2 R 20 |
| LI / SI / PR | 122 A8 / 122 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 855 |
| TRA Code | R1-W |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 36,16 |
| Recommended rim size | W10 |
| Permitted rim size | W9 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 292 |
| Outer diameter of tyre [mm]. | 984 |
| Stat. radius (SLR) [mm] | 447 |
| Speed Radius Index (SRI) | 475 |
| Rolling circumference [mm]. | 2977 |
| Tread depth (mm) | 37,5 |
| Number of lugs | 17x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 122 A8 | 1500 | 40 | | 2,40 | |
| 122 B | 1500 | 50 | | 2,40 | |