

## WHEELS

Product group	Wheels
Item number	10002034
Valid wheel size	405 / 70 R 20
Brand	Dunlop
Tread pattern	SP-T9
Valid rim size	13 x 20
Rim connection	8/221/275
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	25
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp  
Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 11285091
LI / SI / PR	168 A2 / 152 J
Load capacity 1 [kg]	5600
Speed 1 [km/h].	10
Load capacity 2 [kg]	3550
Speed 2 [km/h].	100
M+S	M+S
TRA Code	L2 E2
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	113,15
ECE regulation number	ECE 54
Section width (mm)	401
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3230
Tread depth (mm)	20,0
Tyre capacity 75% [ltr.]	160
E-Ready	No
Assembly Item no. Rim	• 10001498
Load capacity of rim 1 [kg]	4750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	6,00
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27.0
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC

---

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade