

RIMS

| | |
|---------------------------------|------------|
| Product group | Rims |
| Item number | 10002047 |
| Valid rim size | 8.5 - 20 |
| Rim connection | 10/281/335 |
| Bolt hole design | B33 |
| Offset (mm) | +172 |
| Half centre distance (HMA) [mm] | 187 |
| Rim colour | Black |
| Brand | Jamak |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 9500 |
| Speed Rims 1 [km/h] | 25 |
| Load capacity of rim 2 [kg] | 6000 |
| Speed Rims 2 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 72,30 |
| Hump | kein Hump |
| Single / multi-part | mehrteilig |
| Quantity multi-piece | four-part |
| Rim material | steel |

| | |
|---|------------------|
| RAL | RAL9005 |
| Cavity Sealed | No |
| Rim design industry | Standard |
| Disc thickness [mm] | 15 |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Number of additional holes | 2 |
| Additional pitch circle diameter [mm]. | 9.5 |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | M22 DS 36 |
| Bolt hole diameter [mm] | 26 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15x121 |
| Preassembled valve | No |