

## WHEELS

Product group	Wheels
Item number	10002062
Valid wheel size	500 / 45 - 20
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	16 x 20
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	2120
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15212563
LI / SI / PR	134 A8 / 147 A8, 12 PR
Load capacity 1 [kg]	2120
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,53
ECE regulation number	ECE 106
Section width (mm)	490

Stat. radius (SLR) [mm]	433
Rolling circumference [mm].	2820
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 33060176
Load capacity of rim 1 [kg]	6900
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	5800
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade