

WHEELS

Product group	Wheels
Item number	10002073
Valid wheel size	710 / 50 R 26.5
Brand	Alliance
Tread pattern	390
Valid rim size	AG 24.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	6300
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15215745
LI / SI / PR	172 D
Load capacity 1 [kg]	6300
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	255,12
ECE regulation number	ECE 106
Section width (mm)	730
Stat. radius (SLR) [mm]	627

Dynamic radius [mm]	647.1
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4100
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 33060572
Load capacity of rim 1 [kg]	10650
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7850
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade