

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 10002074           |
| Valid wheel size                  | 710 / 50 R 26.5    |
| Brand                             | Alliance           |
| Tread pattern                     | 885                |
| Valid rim size                    | AG 24.00 x 26.5 H2 |
| Rim connection                    | 10/281/335         |
| Bolt hole design                  | A3                 |
| Rim colour                        | Silver             |
| Load capacity complete wheel [kg] | 6000               |
| Speed complete wheel [km/h]       | 65                 |



## Technical Informations

|                            |              |
|----------------------------|--------------|
| Assembly Item no. Tyres    | • 15216255   |
| LI / SI / PR               | 170 D        |
| Load capacity 1 [kg]       | 6000         |
| Speed 1 [km/h].            | 65           |
| Carcass properties         | Steel Belted |
| Antistatic                 | No           |
| Tyre colour                | Black        |
| Nettogewicht [kg] (gültig) | 238,13       |
| ECE regulation number      | ECE 106      |
| Section width (mm)         | 733          |
| Stat. radius (SLR) [mm]    | 629          |

|                             |                               |
|-----------------------------|-------------------------------|
| Dynamic radius [mm]         | 647.1                         |
| Speed Radius Index (SRI)    | 650                           |
| Rolling circumference [mm]. | 4290                          |
| Tread depth (mm)            | 26,0                          |
| Number of lugs              | 21x2                          |
| E-Ready                     | No                            |
| Assembly Item no. Rim       | • 33060572                    |
| Load capacity of rim 1 [kg] | 10650                         |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 7850                          |
| Speed Rims 2 [km/h]         | 65                            |
| Maximum speed [km/h].       | 65                            |
| Maximum air pressure [bar]. | 4,00                          |
| Type of drive               | Angetriebene & gezogene Achse |
| Hump                        | H2                            |
| Valve protection            | VS H                          |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Cavity Sealed               | No                            |
| Ventilation holes           | No                            |
| Verschweißung beidseitig    | No                            |
| Rim centering               | BC                            |
| Number of bolt holes        | 10                            |
| Bolt hole design EUWA       | B22 ES 36                     |
| Bolt hole diameter [mm]     | 27                            |
| Countersinking              | Sphere                        |

---

|                                |                |
|--------------------------------|----------------|
| Spherical countersink [mm].    | R18            |
| hub hole diameter [mm].        | 281            |
| Bolt hole circle diameter [mm] | 335            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 15.7           |
| Preassembled valve             | No             |
| Valve design                   | Rubber valve   |
| Valve length [mm]              | 55.0           |
| Valve angle [°]                | gerade         |