

WHEELS

Product group	Wheels
Item number	10002084
Valid wheel size	500 / 55 - 20
Brand	Alliance
Tread pattern	FarmPRO 327
Valid rim size	16 x 20
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-55
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212559
LI / SI / PR	143 A8 / 155 A8, 12 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	40
Load capacity 2 [kg]	3875
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	97,31
ECE regulation number	ECE 106
Section width (mm)	503

Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3063
Tread depth (mm)	13,5
E-Ready	No
Assembly Item no. Rim	• 10001562
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3800
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,25
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade