

TYRES

Product group	Tyres
Item number	10002098
Valid tyre size	520 / 85 R 38
LI / SI / PR	155 A8 / 155 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Sonderpostenkategorie	DOT
type of damage	DOT



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Technical Informations

Item number	10002098
EAN	4040658117138
Valid tyre size	520 / 85 R 38
Alternative size 1	20.8R38
LI / SI / PR	155 A8 / 155 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	203,10
Recommended rim size	DW18L
Permitted rim size	DD16L, W16, DW16L, W18L
Maximum air pressure [bar].	1,60
Section width (mm)	555
Outer diameter of tyre [mm].	1830
Stat. radius (SLR) [mm]	850
Rolling circumference [mm].	5465
Tread depth (mm)	52,0
Tyre capacity 75% [ltr.]	490
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		1,60	
155 B	3875	50		1,60	