## Bohnenkamp Moving Professionals

19.09.2024

#### TYRES

Product group	Tyres
Item number	10002104
Valid tyre size	380 / 85 R 24
LI / SI / PR	131 A8 / 131 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Sonderpostenkategorie	DOT
type of damage	DOT



TYRE TECHNOLOGY FOR BEST RESULTS

#### Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10002104
EAN	4040658117190
	4040658117190
Valid tyre size	380 / 85 R 24
Alternative size 1	14.9R24
LI / SI / PR	131 A8 / 131 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	72,57
Recommended rim size	W13
Permitted rim size	W11, W12L, DW13L
Maximum air pressure [bar].	1,60
Section width (mm)	400
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3710
Tread depth (mm)	43,4
Tyre capacity 75% [ltr.]	155
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		1,60	
131 A8	1950	40		1,60	

19.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.