

## **TYRES**

Product group	Tyres	
Item number	10002108	
Valid tyre size	445 / 45 R 19.5	
LI / SI / PR	160 J	
TL/TT	TL	
Brand	Continental	
Tread pattern	Conti Hybrid HT3+	





## Notes and features

- The Continental Hybrid HT3+ is a truck trailer tyre for mixed use in regional, local and long-distance traffic.
- It is suitable for all weather conditions, including winter road conditions.
- Its tread pattern with 4 circumferential grooves and improved pocket sipes guarantees perfect grip.
- The special rubber compound ensures low heat generation and lower fuel consumption.



## **Technical Informations**

Item number	10002108		
EAN	4019238071283		
Valid tyre size	445 / 45 R 19.5		
LI / SI / PR	160 J		
TL/TT	TL		
Brand	Continental		
Tread pattern	Conti Hybrid HT3+		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	TR		
Rolling resistance	В		
Wet grip	С		
Rolling noise [db].	73		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	69,50		
Recommended rim size	14.00		
Permitted rim size	15.00		
Maximum air pressure [bar].	9,00		
Section width (mm)	422		
Tread width (mm)	367		
Outer diameter of tyre [mm].	898		
Stat. radius (SLR) [mm]	414		
Rolling circumference [mm].	2775		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Tread depth (mm)	12,8
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100	Single	9,00	