

## WHEELS

Product group	Wheels
Item number	10002112
Valid wheel size	455 / 40 R 22.5
Brand	Bohnenkamp
Tread pattern	Agrarmax MZL
Valid rim size	14.00 x 22.5
Rim connection	10/281/335
Bolt hole design	M22
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 19911657
LI / SI / PR	160 J
Load capacity 1 [kg]	4500
Speed 1 [km/h].	100
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	121,98
ECE regulation number	not necessary
Type of retreading	Cold retreaded (tread)
Section width (mm)	436

Stat. radius (SLR) [mm]	440
Rolling circumference [mm].	2860
Tread depth (mm)	15,0
E-Ready	No
Assembly Item no. Rim	• 10000374
Load capacity of rim 1 [kg]	5500
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26.0
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	HB
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	14.0
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No

---

Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade