

## WHEELS

Product group	Wheels
Item number	10002119
Valid wheel size	700 / 50 - 26.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	AG 24.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15712855
LI / SI / PR	162 A8 / 174 A8, 16 PR
Load capacity 1 [kg]	4750
Speed 1 [km/h].	40
Load capacity 2 [kg]	6700
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	231,35

ECE regulation number	ECE 106
Section width (mm)	700
Stat. radius (SLR) [mm]	581
Speed Radius Index (SRI)	575
Rolling circumference [mm].	4017
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 33060574
Load capacity of rim 1 [kg]	10550
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7750
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,40
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel

---

<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Ventilation holes</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade