

WHEELS

Product group	Wheels
Item number	10002125
Valid wheel size	600 / 55 - 26.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712825
LI / SI / PR	159 A8 / 170 A8, 16 PR
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	6000
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	207,84
ECE regulation number	ECE 106

Section width (mm)	600
Stat. radius (SLR) [mm]	581
Speed Radius Index (SRI)	575
Rolling circumference [mm].	4017
Tread depth (mm)	26,0
Number of lugs	32x2
E-Ready	No
Assembly Item no. Rim	• 10001303
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,60
Number of bolt holes	8
Bolt hole design EUWA	B18 ES 32
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade