

## TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 10002137        |
| Valid tyre size | 710 / 50 R 30.5 |
| LI / SI / PR    | 173 D           |
| TL/TT           | TL              |
| Brand           | Alliance        |
| Tread pattern   | 882             |



## Notes and features

- Newly-developed flotation tyre with steel belt reinforcement.
- Primary use on heavy transport vehicles and slurry tankers as well as manure spreaders with mixed road and field use.
- Directional block tread pattern for low rolling resistance and very good self-cleaning.
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure.
- Steel belt offers additional protection against punctures.

## Technical Informations

|                                 |                 |
|---------------------------------|-----------------|
| Item number                     | 10002137        |
| EAN                             | 8903635050995   |
| Valid tyre size                 | 710 / 50 R 30.5 |
| LI / SI / PR                    | 173 D           |
| TL/TT                           | TL              |
| Brand                           | Alliance        |
| Tread pattern                   | 882             |
| Carcass properties              | Steel Belted    |
| Antistatic                      | No              |
| Tyre colour                     | Black           |
| ECE regulation number           | ECE 106         |
| Nettogewicht [kg] (gültig)      | 187,30          |
| Recommended rim size            | AG24.00         |
| Maximum air pressure [bar].     | 4,00            |
| Section width (mm)              | 727             |
| Outer diameter of tyre [mm].    | 1485            |
| Stat. radius (SLR) [mm]         | 670.1           |
| Speed Radius Index (SRI)        | 700             |
| Rolling circumference [mm].     | 4485            |
| Contact area [cm <sup>2</sup> ] | 2361.1          |
| Tread depth (mm)                | 25,0            |
| Tyre capacity 75% [ltr.]        | 385.50          |
| E-Ready                         | No              |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 173 D | 6500               | 65           |               | 4,00                     |              |