

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10002138 |
| Valid tyre size | 33.25 R 29 |
| LI / SI / PR | 209 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Earthmax SR 32 |



Notes and features

- The BKT Earthmax SR 32 is an EM radial tyre for dumpers and scrapers.
- Its strong all-steel carcass and the cut and puncture-resistant rubber compound ensure a long service life.
- The non-directional tread pattern with its robust blocks enables very good traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10002138 |
| EAN | 8903094057986 |
| Valid tyre size | 33.25 R 29 |
| LI / SI / PR | 209 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Earthmax SR 32 |
| TRA Code | E3 |
| Star Rating | ** |
| Carcass properties | C.R. |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 855,74 |
| Recommended rim size | 27.00/3.5 |
| Permitted rim size | 26.00/3.5 |
| Maximum air pressure [bar]. | 5,25 |
| Section width (mm) | 845 |
| Outer diameter of tyre [mm]. | 2080 |
| Stat. radius (SLR) [mm] | 915 |
| Rolling circumference [mm]. | 6250 |
| Tread depth (mm) | 54,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 209 B | 18500 | 50 | | 5,25 | |