Bohnenkamp Moving Professionals

21.09.2024

RIMS

Product group	Rims
Item number	10002139
Valid rim size	TW 16 L x 46
Rim connection	12/351/400
Bolt hole design	B3
Offset (mm)	-30
Rim colour	Silver
Brand	Moveero

Technical Informations

Load capacity of rim 1 [kg]	6700
Speed Rims 1 [km/h]	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	191,40
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	351
Bolt hole circle diameter [mm]	400
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No