Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	10002141
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	M22
Offset (mm)	+55
Rim colour	Silver
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	65
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	100
Load capacity of rim 3 [kg]	3450
Speed Rims 3 [km/h]	40
Load capacity of rim 4 [kg]	4050
Speed of wheels 4 [km/h].	25
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,00

Technical Informations

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No