

WHEELS

Product group	Wheels
Item number	10002147
Valid wheel size	600 / 55 - 22.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15212648
LI / SI / PR	162 D / 161 E, 16 PR
Load capacity 1 [kg]	4750
Speed 1 [km/h].	65
Load capacity 2 [kg]	4625
Speed 2 [km/h].	70
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	160,59
ECE regulation number	ECE 106

Section width (mm)	600
Stat. radius (SLR) [mm]	550
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3650
Tread depth (mm)	30,0
E-Ready	No
Assembly Item no. Rim	• 33060408
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	70
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade