

TYRES

Product group	Tyres
Item number	10002302
Valid tyre size	17.5 - 25
LI / SI / PR	24 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936



Notes and features

- Rugged tyre for mobile excavators in the harshest of operating conditions.
- Well-suited for road travel.
- Aggressive tread pattern for high traction and good self-cleaning properties.
- High level of stability in use and good handling on the road.

Technical Informations

Item number	10002302
EAN	8903094066643
Valid tyre size	17.5 - 25
LI / SI / PR	24 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936
TRA Code	E2/L2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	127,24
Recommended rim size	14.00/1.5
Maximum air pressure [bar].	7,00
Section width (mm)	450
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	600
Rolling circumference [mm].	4060
Tread depth (mm)	26,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	10000	10	Loader dozer	7,00	
	7700	30	Loader dozer	7,00	
	7000	40	Loader dozer	7,00	