

## TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 10002306      |
| Valid tyre size | 23.1 - 26     |
| LI / SI / PR    | 172 A2, 16 PR |
| TL/TT           | TL            |
| Brand           | Maxam         |
| Tread pattern   | MS931 LOGXTRA |



**MAXAM**

## Notes and features

- The Maxam MS931 LOGXTRA is a bias forestry tyre for skidders, loggers and similar forestry machines.
- Its high-strength, steel-reinforced construction ensures excellent traction.
- The robust tyre shoulder and sidewall as well as the cut-resistant rubber compound protect the tyre from damage.
- The particularly large contact area guarantees very good flotation on wet and muddy ground.
- The nylon-wrapped tyre bead prevents the tyre from coming off the rim during forestry work in difficult conditions.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 10002306      |
| EAN                          | 6959655434477 |
| Valid tyre size              | 23.1 - 26     |
| LI / SI / PR                 | 172 A2, 16 PR |
| TL/TT                        | TL            |
| Brand                        | Maxam         |
| Tread pattern                | MS931 LOGXTRA |
| TRA Code                     | LS-2          |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 280,20        |
| Recommended rim size         | DW20B         |
| Maximum air pressure [bar].  | 2,75          |
| Section width (mm)           | 580           |
| Outer diameter of tyre [mm]. | 1620          |
| Stat. radius (SLR) [mm]      | 747           |
| Speed Radius Index (SRI)     | 775           |
| Rolling circumference [mm].  | 4980          |
| Tread depth (mm)             | 58,0          |
| Number of lugs               | 15x2          |
| Tyre capacity 75% [ltr.]     | 442           |
| E-Ready                      | No            |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 172 A2 | 6300               | 10           |               | 2,75                     |              |