

WHEELS

Product group	Wheels
Item number	10002308
Valid wheel size	400 / 70 R 20
Brand	Alliance
Tread pattern	585
Valid rim size	13 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	+30
Rim colour	Anthrazit
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15285420
LI / SI / PR	149 A8 / 149 B
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Load capacity 2 [kg]	3250
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,55
ECE regulation number	ECE 106
Section width (mm)	404

Stat. radius (SLR) [mm]	485
Rolling circumference [mm].	3237
Tread depth (mm)	30,0
Number of lugs	22x2
E-Ready	No
Assembly Item no. Rim	• 33060161
Load capacity of rim 1 [kg]	4750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL7016
Cavity Sealed	No
Disc thickness [mm]	10
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	27.0
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade