

WHEELS

Product group	Wheels
Item number	10002309
Valid wheel size	385 / 55 R 22.5
Brand	Sailun
Tread pattern	STR1+
Valid rim size	11.75 x 22.5 H
Rim connection	10/281/335
Bolt hole design	M22
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	110



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066369
LI / SI / PR	160 K (158 L), 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	110,53
ECE regulation number	ECE 54 ECE 117 Vecto Certificate
Section width (mm)	385
Rolling circumference [mm].	3018
Tread depth (mm)	15,0
Rolling resistance	C
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10000370
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	120
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	11.0
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
Bolt hole diameter [mm]	26.0

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No