

WHEELS

Product group	Wheels
Item number	10002311
Valid wheel size	710 / 40 R 22.5
Brand	BKT
Tread pattern	FL 635
Valid rim size	AG 24.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4625
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715168
LI / SI / PR	161 D
Load capacity 1 [kg]	4625
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	196,81
ECE regulation number	ECE 106
Section width (mm)	727
Stat. radius (SLR) [mm]	510

Speed Radius Index (SRI)	550
Rolling circumference [mm].	3467
Tread depth (mm)	24,5
E-Ready	No
Assembly Item no. Rim	• 33060461
Load capacity of rim 1 [kg]	10700
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	9200
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade