

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 10002332 |
| Valid tyre size | VF 520 / 85 R 30 CFO + |
| LI / SI / PR | 172 A8 |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | CerexBib 2 |



Notes and features

- The Michelin Cerexbib 2 is a newly-developed tyre for large harvesting machines.
- Its contact area, which is up to 15% larger than that of the CerexBib, provides optimum soil protection.
- All Cerexbib 2 tyres are CFO tyres and therefore suitable for cyclic field operations.
- The Cerexbib 2 has a special casing construction with Ultraflex technology.
- This casing design enables up to 40 higher loading capacities at the same inflation pressure for VF tyres.

Technical Informations

| | |
|---------------------------------|------------------------|
| Item number | 10002332 |
| EAN | 3528701882765 |
| Valid tyre size | VF 520 / 85 R 30 CFO + |
| LI / SI / PR | 172 A8 |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | CerexBib 2 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 179,00 |
| Recommended rim size | W16L |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 522 |
| Outer diameter of tyre [mm]. | 1624 |
| Stat. radius (SLR) [mm] | 709 |
| Speed Radius Index (SRI) | 775 |
| Rolling circumference [mm]. | 4797 |
| Contact area [cm ²] | 2507 |
| Tread depth (mm) | 48,0 |
| Number of lugs | 19x2 |
| Tyre capacity 75% [ltr.] | 435 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 172 A8 | 6300 | 40 | | 2,80 | |